



GYPSUM PLASTERS BROCHURE

False Ceilings | Drywall Partitions | Gypsum Punning | Acoustics
Wall Claddings / Sidings | PVC Paneling | Thermal & Acoustic Insulation

CONTENTS

Sr. No.		Page No.
1.	About KOHINOOR DECOR	3
2.	Gypsum Plasters Range	4
	Gyproc Elite 100	5
	Gyproc Supreme 80	6
	Gyproc Xpert+	7
	Gyproc Elite MS	8
	Gyproc Elite MR	9
	Gypsoman Stucco	10
	Kohinoor Stucco One Coat	11
	Diamond Stucco	12
3.	Notes	13
4.	Contact Us	14

About KOHINOOR DECOR

Who we are?

Incorporated in the year 1998, we 'Kohinoor Decor' are a sole proprietorship-based firm engaged as the foremost wholesale supplier and service provider for Interior designing and False Ceiling Products (Gypsum Plaster, Plaster of Paris, Gypsum Boards, P.O.P. Sheets, Metal Framing Accessories – G.I. Ceiling Sections, Aluminium Ceiling Tiles, Metal Ceiling Tiles, PVC Panels) and False Ceiling Services. Our products are high in demand due to their premium quality and affordable prices. Furthermore, we ensure to timely deliver these products to our clients, through this we have gained a huge client's base in the market. Under the direction of our mentor 'Mr. Mohd. Ilyas Sheikh (Proprietor)', we have been able to achieve a reputed name in the industry.

We, at Kohinoor Decor, one of the most recognized and leading manufacturing and trading firms in Nagpur, provide you with different types of Interior Designing, Gypsum False Ceiling (Residential/ Commercial), Installations, Maintenance or repairing at a professional rate of prescribed designs.

Our business is generally known for its next level ceiling designs, their resistance to extreme weather conditions, ease of services provided and skilled installations by workers.

We also take part in trading all varieties of ceiling products (Gypsum Powder, Gypsum Boards, Ceiling Tiles, Ceiling Sections, Gypsum and Plaster of Paris sheets) at a much cost-effective rate.

From our Executive Owner,

With my 25 years of experience in this stream of interior designing, false ceiling contracts and all related Gypsum works, I have been able to recognize every bit of trading and supplying every commodity in this scenario.

Our business usually deals with better customer satisfaction with every ease of better execution of the work. Our executing staff never fails to perform their tasks regardless of the direction they have been given.

Mohd. Ilyas Sheikh

Owner and Founder at Kohinoor Decor, Nagpur



GYPSUM PLASTERS RANGE



Gypsum plastering is also a faster application method for internal surfaces, since it does not require time consuming water curing process. Water curing process is mandatory for 20 – 21 days after sand-cement plastering to reduce shrinkage cracks arising due to heat of hydration.

Gypsum plaster is mixed with clean water in recommended proportion at site to make a consistent slurry. Gypsum plaster slurry is then applied at desired thickness on walls and ceilings by trained applicators, this process is called as Gypsum plastering.

Gyproc ELITE 100

One Coat Gypsum Plaster



Dry Bulk Density	770 kg/m ³
Water to Powder Ratio	1:1.125
Setting Time	20-25 minutes
Packaging Size	25 kg bag
Applied Thickness	13 mm
Coverage Area	27 sq. ft. per 25 kg bag

Gyproc Elite 100 is a one coat gypsum plaster for use on almost all internal substrates, e.g. brickwork, blocks or concrete. It provides inert, smooth, high quality and durable base for application of decorative finishes over internal walls and ceilings. It is a lightweight, retarded hemihydrate, premixed gypsum plaster, with expanded perlite aggregates, requiring only addition of clean water to prepare it for use.

Gyproc ELITE 100

One Coat Gypsum Plaster



Dry Bulk Density	770 kg/m ³
Water to Powder Ratio	1:1.125
Setting Time	15-20 minutes
Packaging Size	25 kg bag
Applied Thickness	13 mm
Coverage Area	21.5 sq. ft. per 25 kg bag

Gyproc Supreme 80 is a one coat gypsum plaster for use on almost all internal substrates, e.g. brickwork, blocks or concrete. It provides inert, smooth, high quality and durable base for application of decorative finishes over internal walls and ceilings. It is a lightweight, retarded hemihydrate, premixed gypsum plaster, with expanded Vermiculite aggregates, requiring only addition of clean water to prepare it for use.

Gyproc Xpert+ Stucco Gypsum Plaster



Dry Bulk Density	880 kg/m ³
Water to Powder Ratio	1:1.125
Setting Time	10-15 minutes
Packaging Size	20 kg & 25 kg bag
Applied Thickness	13 mm
Coverage Area	18 sq. ft. per 25 kg bag

Gyproc Xpert+ is a stucco gypsum plaster made for application on almost all backgrounds, e.g. brickwork, block work or concrete, suitable for application like POP punning (over Sand & Cement Plaster), bull marks, level strips, etc. It has special additives for enhanced setting time helps in controlling the onsite wastages. It provides perfectly lined and leveled surface providing a perfectly flat surface ready for painting.

Gyproc ELITE MS One Coat Gypsum Plaster



Dry Bulk Density	770 kg/m ³
Water to Powder Ratio	1:1.125
Setting Time	90-120 minutes
Packaging Size	25 kg bag
Applied Thickness	13 mm
Coverage Area	27 sq. ft. per 25 kg bag

Gyproc Elite MS (Machine Spray) is a one coat gypsum plaster for use on almost all backgrounds, e.g. brickwork, block work or concrete. Its special formulation enables spray application through machine giving a significantly lower application cost. It provides a smooth, inert, high quality surface to internal walls and ceilings and a durable base for application of decorative finishes. It is a lightweight, retarded hemihydrate, premixed gypsum plaster requiring only the addition of clean water for plastering.

Gyproc ELITE MR

One Coat Gypsum Plaster



Dry Bulk Density	770 kg/m ³
Water to Powder Ratio	1:1.125
Setting Time	25-35 minutes
Packaging Size	25 kg bag
Applied Thickness	13 mm
Coverage Area	27 sq. ft. per 25 kg bag

Gyproc Elite MR (Moisture Resistant) is a one coat gypsum plaster specifically designed to provide protection in wet areas like bathroom, kitchens, basement, garages, balconies, parking podium etc. It provides extra protection with low absorption of moisture in air or from surface giving excellent results in skirting area application with problems arising out of capillary action and efflorescence. It can be directly used over backgrounds like bricks, blocks, RCC etc and provides a smooth inert, high quality surface to internal walls and ceilings and a durable base for application of decorative finishes.

Gypsoman STUCCO

Gypsum Powder



Dry Bulk Density	700 kg/m ³
Water to Powder Ratio	1:1.38
Setting Time	15-20 minutes
Packaging Size	25 kg bag
Applied Thickness	Upto 13 mm
Coverage Area	28 sq. ft. per 25 kg bag

Gypsoman Stucco Plaster is a good choice for remodeling and repair works. It delivers beautiful and quality cornices and decorations. Gypsoman Stucco Plaster is excellent for the creation of refined textures and smooth surfaces that are free of crack and chip. It creates healthy and aesthetic indoor ambiance.

KOHINOOR STUCCO ONE COAT Gypsum Plaster



Dry Bulk Density	700 kg/m ³
Water to Powder Ratio	1:1.3
Setting Time	40-50 minutes
Packaging Size	20 kg & 25 kg bag
Applied Thickness	Upto 12 mm
Coverage Area	32 sq. ft. per 25 kg bag

Kohinoor Stucco One Coat Gypsum Plaster is a good choice for remodeling and repair works. It delivers beautiful and quality cornices and decorations. Kohinoor Stucco One Coat Gypsum Plaster is excellent for the creation of refined textures and smooth surfaces that are free of crack and chip

Diamond STUCCO Gypsum Plaster



Dry Bulk Density	700 kg/m ³
Water to Powder Ratio	1:1.2
Setting Time	60-70 minutes
Packaging Size	16 kg, 20 kg & 25 kg bag
Applied Thickness	Upto 12 mm
Coverage Area	30 sq. ft. per 25 kg bag

This is the regular Gypsum Powder which is best suitable for giving finishing touches to the designed ceiling. It can also be used for Gypsum punning purposes and many more.

